



PRODUCT BROCHURE

INTRODUCING BERECO

High Performance Bespoke Timber Windows & Doors

Bereco is a premium supplier of high quality, high specification timber windows and doors to both the trade and retail sectors. Selling nationally, Bereco provides truly bespoke products for the prestigious new build and replacement market.

"Excellent quality product, service second to none."

Peter Burton Taylor Wimpey South Midlands



timBER/ECO-friendly

The 'Bereco' brand name is derived from a combination of the words timber and eco-friendly reflecting a continued commitment to the use of environmentally friendly practices. All products are manufactured using 100% FSC timber responsibly sourced from well-managed, certified forests.



Delivering the Difference

Bereco offers a friendly, reliable approach to customer service with highly experienced knowledgeable staff to guide you through every step of the process. We offer design inspiration and technical support in combination with fully itemised quotations and detailed CAD drawings.



Choice & Flexibility

Our product ranges are second to none in the market with products supplied from the same source at the same time, sympathetically designed to incorporate an extensive collection of individual products to suit all properties. Whether you are replicating an existing design or creating a new and inspiring look we offer ironmongery, colour and design choice to complement the internal and external aesthetics of your project.



Outstanding Quality

We are committed to ensuring that high quality remains consistent throughout our entire product range. We use only the finest paint system, engineered timber, hinges, and ironmongery. The greatest aesthetical appeal is combined with ease of maintenance and superior performance. Our accreditation to the BM TRADA Q Mark Scheme is testament to the quality of our products; we are one of a limited number of manufacturers able to achieve such stringent criteria.

p.2



Contemporary Sliding Sash Spiral Balance | RAL 9016 Traffic White | 16mm Bar

p.3

CONTENTS

A guide to our Product Range	4
PRODUCT	5-27
ipped Casement Contemporary	5
ipped Casement Traditional	6
lush Casement Traditional	8
Sliding Sash Spiral Balance Contemporary	10
Sliding Sash Spiral Balance Traditional	12
Sliding Sash Cords & Weights Contemporary	14
Sliding Sash Cords & Weights Traditional	14
ipped French Door Contemporary	16
lush French Door Traditional	16
Sliding Patio Door	18
Sliding Folding Door	20
ENTRANCE DOOR RANGE	22-25
Entrance Door Classic Range	23
Entrance Door Creative Range	24
Entrance Door Heritage Range	25
HERITAGE RANGE	26
GALLERY	28-33
SPECIFICATION	34-43
Contemporary Range	35
raditional Range	37
Heritage Range	40
Entrance Door Range	42
Peace of Mind	43
ENVIRONMENT	44-45
DESIGN	46-51
RONMONGERY	52-53
SECTIONS	54-57
Resources	58

An extensive collection of product designs to suit your property style

contemporary range

Sleek, modern designs with the latest high performance features. Products are specifically designed for new build properties where a modern, contemporary finish is desired.

Traditional Range

Well suited to prestigious new build properties and the traditional replacement market. Designs combine modern operation with classical aesthetics that meet conservation requirements.

Heritage Range

Specifically designed for listed buildings and where conservation approval is required. Designs utilise Single or Slimline glazing options with Lambs Tongue profiling, suitable for the most architecturally sensitive of projects.

ENTRANCE DOORS

Our Range of Classic, Creative and Heritage doors offer time honoured, contemporary or period door styles. Designs incorporate modern security features without compromising on aesthetics.


IRONMONGERY

Our extensive collection of exclusive ironmongery incorporates a vast assortment of design options from traditional classical pieces to the latest Italian designer styles.



p.4

Contemporary Sliding Sash Spiral Balance | RAL 9001 Cream | 16mm Bar





Traditional Lipped Casement | RAL 9016 Traffic White | 6mm Lead Antique Black



oped Casement | RAL 9016 Traffic White | 6mm Lead Antique Black

contemporary range Lipped Casement

The opening out, Contemporary Lipped Casement is the most frequently chosen timber window design in the UK. The profile is often referred to as 'Stormproof' reflecting a proven ability to withstand exposure to adverse weather conditions. Internally glazed with a modern concealed multi point locking system the design provides high security features compliant with Secured by Design conditions. The sash stands proud of the frame giving excellent gasket compression resulting in one of the best weather ratings on the market.

Pencil Round aesthetics create sleek visual lines offering the ideal canvas for creating a truly unique finish. This versatile window can be supplied with various design options and is suited to properties where a modern finish is desired.

Specification Ideas:

- Paint Finish: RAL 7024 Graphite Grey
- Ironmongery: Polished Chrome Bar Pattern: Horizontal Bar 16mm • Unit Spacer: Silver
- Why not try: A Dual Colour Finish



Traditional Lipped Casement | Traditional Classic Entrance Door | RAL 9016 Traffic White | Door Leaf: RAL 9005 Jet Black | 6mm Lead Antique Black

Traditional Range

Lipped Casement

A period style window with distinctive traditional aesthetics, the Traditional Lipped Casement offers a modern method of operation with enhanced security features as standard. Creating a lipped profile the sash stands proud of the frame, ideal for period properties where extra protection from the elements is required.

Excellent sound proofing properties are achieved with a double weather seal around the sash and friction hinges are used to provide modern functionality. Available in both top and side hung styles this period design incorporates internal Ovolo mouldings and external Putty Line design, consistent throughout the Traditional Range. Approved by conservation officers and used in English Heritage projects across the UK, the design retains traditional features whilst enhancing charm and character.


pecification Ideas:

• Paint Finish: RAL 1015 Light Ivory • Ironmongery: Satin Chrome
Bulb End • Bar Pattern: Cottage Bar 25mm • Unit Spacer: Warm
Edge, Grey • Why not try: 6mm Silver Lead



Traditional Flush Casement | RAL 9016 Traffic White | 6mm Lead Antique Black

p.8



Traditional Range

Flush Casement

Our most traditional window, the Flush Casement, is specifically designed to replicate a period window whilst incorporating the latest modern operation and security features. Often referred to as a conservation window, the design is characterised by a sash that sits within the frame to create a flush finish externally, the perfect choice for listed properties.

To further accentuate external features, decorative butt hinges, deeper bottom sash rails and sub cill options are incorporated into the design. Concealed hinges offer modern operation, whilst casement stays offer a traditional finish complementing ironmongery choice to match interior décor. Internal Ovolo mouldings and external Putty Line design replicate the simplistic yet elegant profiling consistent throughout the Traditional Range. Designs incorporate an openable fixed sash for ease of installation, ideal for use in refurbishment properties.


Specification Ideas:

- Paint Finish: RAL 1013 Oyster White Ironmongery: Monkey Tail Black Bar Pattern: Georgian Bar 16mm Lambs Tongue
- Unit Spacer: Warm Edge Black Why not try: 6mm Antique Black Lead



Contemporary Sliding Sash Spiral Balance | RAL 9001 Cream | 16mm Bar

p.10



contemporary range

A modern interpretation of the original Sliding Sash window, the Contemporary Spiral Balance is ideal for new build properties combining style with high security and excellent weather ratings second to none on the market.

The latest Inline Balance technology is used to operate the window and concealed rickle vent detail offers functionality without compromising on aesthetics. To complete the sleek appearance, the Contemporary Range Spiral Balances feature Pencil Round mouldings, consistent throughout the Contemporary Range. Decorative horns ympathetically designed to match the overall appearance of the windows are included as standard to the top sash.

This design offers an energy efficient, cost effective solution whilst retaining all the unique design features of a Sliding Sash window.

Specification Ideas:

Paint Finish: RAL 9016 Trattic White • Ironmongery:
 Polished Chrome • Bar Pattern: Marginal Bar 16mm • Unit
 Spacer: Warm Edge, White • Why not try: Deluxe Acorn
 Fastener, Satin Chrome



Indulional Stiding Sasti Spiral Balance | KAL 9010 Trailic White | Tollin Bar (Lambs longue



Traditional Sliding Sash Spiral Balance | RAL 9001 Cream | 25mm Bar


Traditional Range

Sliding Sash - Spiral Balance

A traditional design manufactured in a modern way, the Traditional Sliding Sash Spiral Balance combines all the features of an original Sliding Sash window with modern high performance and security features. The latest Inline Balance technology and a concealed trickle vent detail have been incorporated into the design without detracting from the windows traditional aesthetics. Attractive Angel VentlocksTM offer simple and user friendly sash locking, easily operated by the homeowner.


Elegant period styling is combined with one of the best weather ratings for Sliding Sash on the market. External Putty Line design and internal Ovolo mouldings replicate original profiling with a traditional horn detail, exclusive to the Range. This window is ideal where a period finish is desired, enhancing a building's exterior façade and complementing interior décor.






Specification Ideas:

- Paint Finish: Linen Ironmongery: Brass Bar Pattern: Georgian Bar 16mm Lambs Tongue
- Unit Spacer: Warm Edge, White Why not try: Deluxe Bee-hive Fastener, Brass



Contemporary Sliding Sash Cords & Weights | RAL 9016 Traffic White | 16mm Bar



contemporary range Sliding Sash - Cords & Weights

Combining a Pulley and Weight method of operation with a sleek modern profile the Contemporary Sliding Sash Cords & Weights offers a subtle mixture of old and new.

This design is ideal where specific build circumstances dictate or when conservation requirements are a consideration. Available up to 1350mm in width and 3000mm in height, a practical solution is offered for projects where much larger Sliding Sash window sizes are required. Available with an optional Simplex Easy Clean System to allow cleaning of the outer face of the sash from inside the property. With excellent weather ratings, the latest high security sash locking and hidden trickle vent detail this modern design is perfect for 21st century living

specification Ideas:

Paint Finish: Parchment • Ironmongery:
 Polished Chrome • Bar Pattern: Vertical Bar
 16mm • Unit Spacer: Silver • Why not try:
 Deluxe Bee-hive Fastener, Polished Chrome

Traditional Range


Sliding Sash - Cords & Weights

The perfect representation of an original Sliding Sash, the Traditional Cords & Weights window incorporates the same traditional method of operation as the Contemporary profile with the addition of period aesthetics. Classically styled, the design replicates the opulence and grandeur of historic sash windows.

Authentic traditional external Putty Line design and internal Ovolo mouldings accentuate the existing character of a period property. Featuring exclusive horn detail to the top sash as standard, an internal horn option to the bottom sash is available further enhancing interior decor. Offering an excellent weather and energy rating this sympathetic design incorporates high performance features without detracting from original aesthetics.

Specification Ideas:

Paint Finish: Parlour • Ironmongery: Claw
 Fastener Antique Black • Bar Pattern:
 Georgian Bar 25mm • Unit Spacer: Warm
 Edge, White • Why not try: Horns to Top &
 Bottom Sash






Contemporary French Door Lipped | RAL 9001 Cream | 25mm Bar



Contemporary French Door Lipped | RAL 9016 Traffic White | 9mm Lead



Traditional French Door Lipped | RAL 9016 Traffic White | 25mm Bar



contemporary**range**Lipped French Door

Bring the outdoors in whilst creating a truly modern finish to any project with the Contemporary Lipped French door. The design is available in a number of single and double door leaf configurations with inward or outward opening options. The Lipped French Door gives you the versatility to maximise internal and external spaces.

deal for use in conservatories or garden rooms this modern design combines a Stormproof profile and sleek Pencil Round mouldings that match perfectly with other Contemporary Range products. With one of the thickest door leafs on the market at 68mm the design offers superior quality and a robust feel. High performance design options include thermally insulated panels, espagnolette locking, 3D adjustable hinges and Stormguard aluminium thresholds on inward opening designs.

Specification Ideas:

- Paint Finish: RAL 9010 Pure White
- Ironmongery: Satin Chrome Bar Pattern:
 None Unit Spacer: Silver Why not try:
 A Curved Fanlight
- *Also available in the Iraditional Range

Traditional Range


Flush French Door

The perfect way to introduce maximum light into any room; the Traditional Flush French Door can be designed to incorporate a number of single and double door leaf configurations. Available opening in where external space is limited on balcony areas or opening out to maximise internal living space, this versatile product can be designed to suit any project.

Period features including double handle and deeper panel profiling are combined with the latest 3D adjustable hinges, thermally insulated panels and high security espagnolette locking system. Perfectly complementing the Traditional Flush Casement, this product is suitable for conservation areas and ideal for enhancing traditionally styled sunrooms and orangeries.

Specification Ideas:

Paint Finish: French Green • Ironmongery:
 Antique Black • Bar Pattern: Cottage Bar
 25mm • Unit Spacer: Silver • Why not try:
 Balmoral Swan Handle, Polished Chrome






Contemporary Sliding Patio Door | RAL 9016 Traffic White | Ironmongery: Silver



Traditional Sliding Patio Door | RAL 9016 Traffic White | Ironmongery: Silver

Make the most of your living space



contemporary range Traditional Range

Sliding Patio Door

Sliding Patio Doors provide the perfect solution for creating vast open plan areas without encroaching on external space or clashing with interior furnishing. This design offers the ideal solution for creating large glazing areas with minimal timber allowing for uninterrupted views to be enjoyed from a property.

Available in both Contemporary & Traditional profiles this versatile design can be manufactured with single leaf sizes of up to 3 metres wide, offering an overall frame size of 6 metres for a double leaf configuration. An innovative lift and glide system allows the homeowner to slide large, heavy weight panels effortlessly. A low level threshold gives a seamless transition between indoor and outdoor living.

Suggested Specification:

• Paint Finish: RAL 7015 Slate Grey • Ironmongery: Silver • Bar Pattern: None • Unit Spacer: Warm Edge, Black • Why not try: A Dual Colour Finish

contemporaryrange Traditional Range Folding Sliding Door

Exterior Folding Sliding Doors are without doubt the new vogue in indoor/outdoor living today. Perfect for connecting or partitioning an outdoor area, folding doors open and close effortlessly and stack unobtrusively to create wide open vistas.

Designs utilise the innovative Brio Top Roller Track System for smooth operation, ease of cleaning with locking technology to ensure panels remain set. Doors can be supplied outward opening from either the left, right or both sides. A unique Floating Door System is available on 4, 6 and 8 leaf units allowing door leaves to stack to the left, right or float in the centre. We offer the single largest folding screen on the market ideal for opening a whole façade in swimming pools and outdoor entertaining areas. Folding Doors are available with Contemporary or Traditional profiling to ensure consistent aesthetics throughout the property.

Suggested Specification:

• Paint Finish: RAL 9016 Traffic White • Ironmongery: Satin Chrome • Bar Pattern: None • Unit Spacer: Silver • Why not try: A Floating Door Model



Folding Door Flush Bolts and matching handles are available in a choice of four premium finishes:




The beauty of the Folding Door is the creation of a seamless transition between inside and out bringing us closer to nature whilst making the most of natural light.

Embrace open plan living

by bringing the outdoors in


At Bereco we offer Folding Doors from 2 leaves up to 10 in a variety of configurations.


- Internal Grip Handle Only
- Internal Grip Handle + External Handle
- F Floating System






Contemporary Folding Door | RAL 9016 Traffic White | Ironmongery: Satin Stainless







CREATE AN ENTRANCE Quality doors with a designer edge

Entrance Door designs are PAS 23/24 certified incorporating the latest high security espagnolette locking system without compromising on aesthetics.

Supplied pre-hung and available inward or outward opening, designs offer flexibility to suit project requirements. High performance fully adjustable 3D hinges from SFS, Stormguard aluminium threshold and a solid 68mm thick door leaf ensures a premium product.



Time honoured classical designs, available in both Traditional and Contemporary profiles.



Exclusively designed contemporary door styles expertly crafted with sleek, flush veneered panels and finished for a statement entrance.

Heritage Range

Uniquely designed timeless period styles reminiscent of the Georgian, Victorian and Edwardian eras.



Contemporary Entrance Door | RAL 9016 Traffic White | 16mm Bar



raditional Entrance Door | RAL 9016 Traffic White | 16mm Bar



Traditional Entrance Door | Frame: Parlour, Leaf: F&B No. 79 Card Room Green

p.22



Luxury Entrance Doors Designed with Style and Substance


The Classic Entrance Door Range utilises time honoured classical designs, available in both Contemporary and Traditional profiles. The range comprises of 14 classically styled front and rear door designs; each can be individually tailored to create a wide variety of bespoke options to suit specific project requirements. This versatile style of door is suitable for any type of home with designs available to complement both modern and period style properties. All designs are also available as double leaf or as a Stable Door (Traditional Range, opening in).



Suggested Specification:

• Paint Finish: Frame: RAL 9016 Traffic White, Leaf: RAL 5016 Cobalt Blue • Ironmongery: Polished Chrome Balmoral • Bar Pattern: None • Unit Spacer: Silver • Why not try: Bevelled or Frosted Glass

Create a Feature Fanlight







An expertly crafted collection of 10 exclusively designed contemporary door styles. The range has been specifically designed with sleek, flush panels to create a truly modern appearance and is available in 4 veneer finishes; Redwood, Meranti, Oak and Larch. The Creative Door Range is the perfect design choice where a unique, statement entrance door is desired. In addition, we have introduced a selection of the latest Italian designer door furniture to complete the look.


The Creative Range offers the highest security and weather performance with an overall U-value of only 0.99W/m²K. This versatile entrance door can add a modern, contemporary twist to a traditionally styled property for that extra special design feature.

Suggested Specification:

- Stain Finish: Oak Veneer with an Oak Stain
- Ironmongery: Satin Chrome Bar Pattern: None Unit Spacer: Silver • Why not try: A Stainless Steel Pull Handle



CR3 Creative Door | Oak Veneer - Light Pine Stain | Ironmongery: Stainless Steel



Create bespoke designs using clear and obscure glass

A range of timber veneers



Sleek flush insulated leaf

A range of Contemporary Furniture

Heritage Range

A timeless collection of 10 sympathetically designed period door styles inspired by the distinctive traditional aesthetics of the Georgian, Victorian and Edwardian eras. The Heritage Door Range combines the latest modern security features, performance and technology whilst retaining the properties historical character and charm.


The most suitable colour finishes and choices of period ironmongery are carefully combined with leaded design options to replicate original aesthetics. Retaining period features is a particularly important consideration where buildings are listed and where specific conservation requirements must be met. Features include deeper timber panels, traditional external Putty Line design and internal Ovolo mouldings to replicate elegant period profiling.

Suggested Specification:

- Paint Finish: Farrow & Ball Elephant's Breath
- Ironmongery: Pewter Bar Pattern: None
- Unit Spacer: Black Warm Edge Why not try: Lead or Bevelled Glass



H1 Heritage Door | Farrow & Ball Stone Blue | Ironmongery: Brass



A range of lead designs available upon request



Raised & Fielded panel



Victorian Ironmongery





Heritage Flush Casement | BS.10.B.17 Oatmeal | Ironmongery: Black Monkey Tail

Heritage Range

Specifically tailored for conservation projects

The Heritage Range has been specifically designed for listed buildings and where conservation approval is required.

Products are available with 4mm Single Glazing or 14mm Slimline Double Glazing options suitable for the most architecturally sensitive of projects where standard double glazing is not appropriate.

Designs incorporate period aesthetics utilising Lambs Tongue profile glazing beads, Putty Line mouldings with a range of Lambs Tongue glazing bars consistent throughout the range.

Single Glazing - 4mm


Single glazing is often insisted upon where strict guidelines govern

Suggested Specification:

• Paint Finish: Farrow & Ball Hardwick White • Ironmongery: Black Monkey Tail • Bar Pattern: 16mm Lambs Tongue • Unit Spacer: White Warm Edge • Why not try: Colour matched internal Architraves

"The windows are fantastic, so quiet, brilliant."

Presenter of Channel 4's Restoration Man



Slimline Glazing - 14mm

Krypton filled as standard, this unit meets the need for traditional looking glazing, whilst importantly still achieving Part L compliance.

PRODUCTS WITHIN THE RANGE

• Flush Casement

The design replicates the original features of a wooden period window. Ideal for the most architecturally sensitive of projects where traditional double glazing is not deemed appropriate.

• Flush French Door

Offering the same period profiling as the Traditional Range whilst incorporating Single or Slimline Glazing, the design perfectly compliments our Heritage Flush Casement.

• Sliding Sash


A Heritage Sliding Sash window design specifically tailored to have the slimmest frame section available on a modern window today. Not only is the frame depth reduced to only 140mm, the sash width is slimmer resulting in maximised glazing areas. The design is perfect for replicating old sash windows as they do not project into the room when behind a reveal.

- Spiral Balance

Featuring a semi-concealed pre-tensioned Spiral Balance combining modern operation with authentic period styling.

- Cords & Weights

Utilising a traditional Cords and Weights mechanism this design is ideal for larger window openings or where external reveals are present.




Sliding Sash Cill Section

Spiral Balance Jamb Section Cords & Weights Jamb Section


Lambs Tongue Bar

The Heritage Range features a selection of Lambs Tongue profile glazing bars available in a range of sizes to suit your design needs. Sizes are available in 16mm, 25mm, 35mm and a 48mm Solid Bar.

Single Glazing



Slimline Glazing



p.26

"For a house to be viewed as successful, window and door architecture is critical. Bereco provides this rare skill and integrity, truly UK's number one"

David Edwards
Winner of Daily Telegraph / Home Building & Renovating UK Traditional House Award



Classic Entrance Door | RAL 9016 Traffic White | Curved Fanlight - Bespoke Bar Pattern 16mm



Contemporary Sliding Sash Spiral Balance | RAL 9016 Traffic White | 16mm Bar





Contemporary French Door Lipped | RAL 9016 Traffic White | 16mm Bar



Traditional French Door | Traditional Lipped Casement | RAL 9016 Traffic White | 6mm Antique Black Lead



Contemporary Folding Door | Contemporary French Door Lipped | Contemporary Fixed Angled Window



Traditional Sliding Sash Spiral Balance | Traditional Flush French Door | RAL 9016 Traffic White | 25mm Bar



Traditional French Door Lipped | Ironmongery: Black Balmoral Swan | 16mm Lambs Tongue Bar



Contemporary Sliding Patio Door | RAL 7003 Moss Grey | Ironmongery: Silver | 16mm Bar



Contemporary French Door Lipped | Contemporary Sliding Sash Spiral Balance | BS.10.B.15 Gardenia | 16mm Bar

BERECO PRODUCT SPECIFICATION All you need to know about our products

GENERAL SPECIFICATION

TIMBER

100% FSC engineered, defect free timber, responsibly sourced from well-managed, certified forests is used across the entire Bereco Product Range.

GLAZING

Products are supplied with Softcoat low-E argon filled double glazing as standard*. Laminated and toughened glazing is available to meet building regulations ensuring the home is safe and secure.

*See page 26 for Heritage Range specialist glazing

FINISH

Designs are supplied fully factory finished as standard; a four stage treatment process is utilised in the application of paint or stain ensuring consistent high quality throughout the product range.

BM TRADA

Bereco is a founding member of the BM TRADA Q Mark Scheme; a high performance licence offering peace of mind as all products are subject to the most rigorous quality control regime and will perform for many years to come.

BS7950 & PAS 23/24

Our products are certified to BS7950 and PAS 23/24 reflecting our commitment to ensuring the highest levels of safety & security.

KITEMARKED PRODUCTS

All Bereco products supplied with laminated (safety) glass are kite marked with the BS logo etched on to the glass.

WEATHER PERFORMANCE - BS6375

Products are tested to BS6375 which rates the weather performance of windows, providing a classification for weather tightness.



Contemporary Sliding Sash Spiral Balance | Painted RAL 7024 Graphite Grey | 16mm Bar

*See p.54 for cill/threshold options

• External Pencil Round Moulding • Internal Contemporary Beading • 24mm Double Glazing



LIPPED CASEMENT

Exclusive Features:

- Easy Clean Friction Hinge
- Stormproof Design
- Anti-Prise Clips (Easy Clean only)
- Espagnolette Locking
- Semi-Concealed Trickle Vent (Ext)

SLIDING SASH (SPIRAL BALANCE)

Exclusive Features:

- Semi-Concealed Inline Spiral Balance
- Decorative Horns to Top Sash • Retractable Vent Lock & Strikeplate
- Concealed Trickle Vent (Ext)



SLIDING SASH (CORDS & WEIGHTS)

Exclusive Features:

- Traditional Pulley & Weight System
- Decorative Horns to Top Sash
- Retractable Vent Lock & Strikeplate
- Concealed Trickle Vent (Ext)

Optional Features:

- 90° Egress Friction Hinge (FE)
- Easy Clean Restrictor Hinge
- Auto-Latch Restrictor
- Dummy Sash (DS)
- Mock Sliding Sash

Optional Features:

- ullet Angel Ventlock $^{ extsf{TM}}$ & Strikeplate
- Horns to Top & Bottom Sash
- No Horns

Optional Features:

- Angel Ventlock™ & Strikeplate
- Horns to Top & Bottom Sash
- No Horns
- Easy Clean Facility (Simplex Fittings)

Standard Specification:

Frame Dimensions

Depth: 68mm. Width: 60mm (Jamb)

Sash Dimensions

Depth: 68mm. Width: 80mm (Stile)

155mm overall (68 + 87mm ext)*

Operation

Window opens outwards Side hung/top hung/fixed (FL)

Mechanism

Handle operated Espag Adjustable locking cams

Easy Clean Friction

Trickle Vent

R13 - 3400 EA per Vent

Standard Specification:

168mm overall (flush)*

Sashes can be fixed

Sashes slide up and down

XS16 - 4600 EA per Vent

Inline Balances (spring loaded)

Rebated into jambs of outer frame

Frame Dimensions

Sash Dimensions

Operation

Mechanism

Trickle Vent

<u>Hinge</u>

N/A

Depth: 168mm. Width: 56mm (Jamb)

Depth: 56mm. Width: 56mm (Stile)

Standard Specification:

Frame Dimensions

Depth: 168mm. Width: 110mm (Jamb)

Sash Dimensions

Depth: 56mm. Width: 56mm (Stile)

168mm overall (flush)*

Operation

Sashes slide up and down Sashes can be fixed

Mechanism

6mm Cord, Steel/Lead Weights Ball Bearing Sash Pulley

Hinge N/A

Trickle Vent

XS16 - 4600 EA per Vent

p.34

• Glazing Bars: 16mm, 25mm, 35mm, 60mm (Solid)



TILT & TURN

Exclusive Features:

- 90° Concealed Hinge
- Concealed Trickle Vent (Ext)
- Concealed Aluminium Bottom Bead
- Espagnolette Locking
- Ideal for Large Sash Openings

Optional Features:

- Dummy Sash (DS)
- Mock Sliding Sash

Standard Specification:

Frame Dimensions

Depth: 68mm. Width: 80mm (Jamb)

Sash Dimensions

Depth: 68mm. Width: 80mm (Stile)

155mm overall (68 + 87mm ext)*

Operation

Window opens inwards Tilt & Turn/turn only/tilt only/fixed (FL)

Mechanism

Handle operated Espag Adjustable locking cams

<u>Hinge</u>

90°Concealed/Exposed

Trickle Vent

R13 - 3400 EA per Vent



FRENCH DOOR (LIPPED)

Exclusive Features:

- Swiss Engineered Adjustable Hinges
- 68mm Deep Door Leaf
- Espagnolette Locking
- Stormguard Aluminium Threshold
- 22mm Deep Weatherbar Design
- 90° Concealed Restrictor (Open Out)

Optional Features:

- Double Handle
- Hinge Covers: White/Brown/Silver
- Split Spindle
- Keyed Alike Cylinder
- Thumb-Turn Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 68mm. Width: 80/100mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 110mm (Stile)

Hardwood 140mm overall*

Operation

Door opens in or out

Single handle. Straight through Spindle

Mechanism

Lead Leaf: Handle operated Espag (3 Point) Slave Leaf: Lever operated Shoot Bolts

SFS Easy 3D (Stainless Steel) Adjustable in 3 dimensions

Trickle Vent

R13 - 3400 EA per Vent



SLIDING PATIO DOOR

Exclusive Features:

- Lift & Glide Mechanism
- 68mm Deep Door Leaf
- Span up to 9 metres
- German Manufactured Hardware
- Hardwood Threshold
- Night Vent Position

Optional Features:

- Trickle Vent R13 3400 EA per Vent
- Locking Handle Int (Half Cylinder) Grip Ext
- Locking Handle Int & Ext
- Handles: White, Silver, Gold
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 171mm Width: 56mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 92mm (Stile)

Hardwood 186mm overall*

Operation

Door slides left/right

Int: Non-locking handle. Ext: Grip

Mechanism

Handle operated Espag (2 Point) Slides horizontally within frame

Concealed Bogie-Runner System

Trickle Vent

None



• External Putty Line Moulding • Internal Ovolo Beading



SLIDING FOLDING DOOR

Exclusive Features:

- Brio Weatherfold 4S System
- 68mm Deep Door Leaf
- Span up to 9 metres
- Range of Designs with up to 10 Leaves
- Matching Hardware
- Track Top Hung

Optional Features:

Standard Specification:

Frame Dimensions

- Trickle Vent XR16 3400 EA per Vent Easy Clean Friction Hinge
- Floating Door System (Models 440/660)
- 196mm Hardwood Threshold
- A Choice of Stained Thresholds

- Easy Clean Restrictor Hinge
- Auto-Latch Restrictor
- Openable Fixed Sash (Easy to Install)
- Anti-Prise Clips

Frame Dimensions

Depth: 153mm Width: 41mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 90mm (Stile)

Aluminium 202mm overall

Operation

Door slides and concertinas left/right Door opens out (top rolling function)

Mechanism

Brio Weatherfold 4S Flush fitting Drop Bolts

Non-Mortice Hinge System

Trickle Vent

None

LIPPED CASEMENT

- 90° Egress Friction Hinge
- Casement Stay

Exclusive Features:

- Slim Frame Section Maximises Glass
- Anti-Warp Clips (Size dependant)
- Night Vent Position

Optional Features:

Standard Specification:

Depth: 73mm Width: 56mm (Jamb)

Sash Dimensions

Depth: 56mm. Width: 68mm (Stile)

160mm overall (73 + 87mm ext)*

Operation Window opens outwards Side hung/top hung/fixed (DS)

Mechanism

Handle operated Espag Adjustable locking cams

<u>Hinge</u>

90° Egress Friction Top hung: Easy Clean Friction

Trickle Vent

R13 - 3400 EA per Vent

FLUSH CASEMENT **Exclusive Features:**

- 90° Concealed Hinae
- Casement Stay
- Decorative Butt Hinge BLK/PB/PC/SC • Night Vent Position
- Anti-Warp Clips (Size dependant) • Clip Out Sash Detail

Optional Features:

- Easy Clean Friction Hinge • Easy Clean Restrictor Hinge
- Auto-Latch Restrictor
- Openable Fixed Sash (Easy to Install)
- Anti-Prise Clips

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 56mm (Jamb) Sash Dimensions Depth: 56mm. Width: 56mm (Stile)

179mm overall (92 + 87mm ext)* Operation

Window opens outwards

Mechanism Handle operated Espag

Side hung/top hung/fixed (DS)

Hinge

90° Concealed GU/Uni-Jet Contura Top hung: Easy Clean Friction

Trickle Vent

R13 - 3400 EA per Vent

Adjustable locking cams

*See p.54 for cill/threshold options

• 24/32mm Double Glazing • Glazing Bars: 16mm (Lambs Tongue), 25mm, 35mm, 48mm (Solid)



SLIDING SASH (SPIRAL BALANCE)

Exclusive Features:

- Semi-Concealed Inline Spiral Balance
- Decorative Horns to Top Sash
- Concealed Trickle Vent (Ext)
- Angel VentLock™ & Strikeplate

Optional Features:

- Retractable Sash Vent Lock & Strikeplate
- Horns to Top & Bottom Sash
- No Horns
- Deep Bottom Rail

Standard Specification:

Frame Dimensions

Depth: 168mm. Width: 56mm (Jamb)

Sash Dimensions

Depth: 56mm. Width: 56mm (Stile)

168mm overall (flush)*

Operation

Sashes slide up and down Sashes can be fixed

Mechanism

Inline Balances (spring loaded) Rebated into jambs of outer frame

<u>Hinge</u> N/A

Trickle Vent

XS16 - 4600 EA per Vent



SLIDING SASH (CORDS & WEIGHTS)

Exclusive Features:

- Traditional Pulley & Weight System
- Decorative Horns to Top Sash
- Concealed Trickle Vent (Ext)
- Angel Ventlock™ & Strikeplate

• 90° Concealed Hinge

TILT & TURN

Exclusive Features:

- Concealed Trickle Vent (Ext)
- Concealed Aluminium Bottom Bead
- Espagnolette Locking
- Ideal for Large Sash Openings

Optional Features:

- Dummy Sash (DS)
- Mock Sliding Sash

- Retractable Sash Vent Lock & Strikeplate
- Horns to Top & Bottom Sash
- No Horns

Optional Features:

- Deep Bottom Rail
- Easy Clean Facility (Simplex Fittings)

Standard Specification:

Frame Dimensions

Depth: 168mm. Width: 110mm (Jamb)

Sash Dimensions

Depth: 56mm. Width: 56mm (Stile)

168mm overall (flush)*

Operation

Sashes slide up and down Sashes can be fixed

Mechanism

6mm Cord, Steel/Lead Weights Ball Bearing Sash Pulley

Hinge

N/A

Trickle Vent

XS16 - 4600 EA per Vent

Standard Specification:

Frame Dimensions

Depth: 68mm. Width: 80mm (Jamb)

Sash Dimensions

Depth: 68mm. Width: 80mm (Stile)

155mm overall (68 + 87mm ext)*

Operation

Window opens inwards Tilt & Turn/turn only/tilt only/fixed (FL)

Mechanism

Handle operated Espag Adjustable locking cams

90° Concealed/Exposed

Trickle Vent

R13 - 3400 EA per Vent



FRENCH DOOR (LIPPED)

Exclusive Features:

- Swiss Engineered Adjustable Hinges
- 68mm Deep Door Leaf
- Espagnolette Locking
- Stormguard Aluminium Threshold
- 22mm Deep Weatherbar Design
- 90° Concealed Restrictor (Open Out)

Optional Features:

- Single Handle
- Hinge Covers: White/Brown/Silver
- Split Spindle
- Keyed Alike Cylinder
- Thumb-Turn Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 68mm. Width: 80/100mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 107mm (Stile)

Hardwood 140mm overall*

Operation

Door opens in or out Double handle. Straight through Spindle

Mechanism

Handle operated Espag (3 Point) and Shoot Bolts

SFS Easy 3D (Stainless Steel) Adjustable in 3 dimensions

Trickle Vent

R13 - 3400 EA per Vent

FRENCH DOOR (FLUSH) Exclusive Features:

- Swiss Engineered Adjustable Hinges
- 68mm Deep Door Leaf
- Espagnolette Locking
- Stormguard Aluminium Threshold
- 22mm Deep Weatherbar Design
- 90° Concealed Restrictor (Open Out)

Optional Features:

- Split Spindle
- Keyed Alike Cylinder
- Thumb-Turn Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 66mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 107mm (Stile)

Threshold Hardwood 140mm overall*

Operation

Door opens in or out Double handle. Straight through Spindle

Mechanism

Handle operated Espag (3 Point) and Shoot Bolts

<u>Hinge</u>

SFS Just 3D (Stainless Steel) Adjustable in 3 dimensions

Trickle Vent

R13 - 3400 EA per Vent

Exclusive Features:

STABLE DOOR (LIPPED)

- Swiss Engineered Adjustable Hinges
- 68mm Deep Door Leaf
- Espagnolette Locking • Stormguard Aluminium Threshold
- 22mm Deep Weatherbar Design
- Lower leaf opens in by T&T handle

Optional Features:

- Trickle Vent R13 3400 EA per Vent
- Hinge Covers: White/Brown/Silver
- Keyed Alike Cylinder
- Thumb-Turn Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions Depth: 68mm. Width: 100mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 107mm (Stile)

Hardwood 140mm overall*

Operation Door opens in

Lever Handle. Straight through Spindle

Mechanism

Handle operated Espag

SFS Easy 3D (Stainless Steel) Adjustable in 3 dimensions

Trickle Vent

None

p.38

Heritage Range

• 4mm Single/14mm Slimline Glazing



• External Putty Line Moulding • Internal Ovolo Beading • Glazing Bars: 16mm, 25mm, 35mm, 48mm (Solid) (LT)





Exclusive Features:

• Traditional Pulley & Weights System

SLIDING SASH (CORDS & WEIGHTS)

- Decorative Horns to Top Sash
- Concealed Trickle Vent (Ext)
- Angel Ventlock™ & Strikeplate

Exclusive Features:

- Swiss Engineered Adjustable Hinges • 68mm Deep Door Leaf
- Espagnolette Locking

FRENCH DOOR (FLUSH)

- Stormguard Aluminium Threshold
- 22mm Deep Weatherbar Design
- 90° Concealed Restrictor (Open Out)

Optional Features:

Exclusive Features:

• Horns to Top & Bottom Sash

• Decorative Horns to Top Sash

Concealed Trickle Vent (Ext)

Angel Ventlock™ & Strikeplate

SLIDING SASH (SPIRAL BALANCE)

• Semi-Concealed Inline Spiral Balance

- No Horns
- Deep Bottom Rail

Optional Features:

- Horns to Top & Bottom Sash
- No Horns
- Deep Bottom Rail

Optional Features:

- Split Spindle
- Keyed Alike Cylinder
- Thumb-Turn Cylinder
- A Choice of Stained Thresholds

SLIDING PATIO DOOR

Exclusive Features:

- Lift & Glide Mechanism
- 68mm Deep Door Leaf • Span up to 9 metres
- German Manufactured Hardware
- Hardwood Threshold
- Night Vent Position

Optional Features:

- Trickle Vent R13 3400 EA per Vent
- Locking Handle Int (Half Cylinder) Grip Ext

Depth: 171mm Width: 56mm (Jamb)

Depth: 68mm. Width: 92mm (Stile)

Int: Non-locking handle. Ext: Grip

Handle operated Espag (2 Point)

Slides horizontally within frame

Concealed Bogie-Runner System

Hardwood 186mm overall*

Door slides left/right

• Locking Handle Int & Ext

Standard Specification:

Frame Dimensions

Leaf Dimensions

Operation

Mechanism

Trickle Vent

None

- Handles: White, Silver, Gold
- A Choice of Stained Thresholds

Optional Features:

• Track Top Hung

Exclusive Features:

SLIDING FOLDING DOOR

• Brio Weatherfold 4S System

• 68mm Deep Door Leaf

• Span up to 9 metres

Matching Hardware

• Trickle Vent - XR16 - 3400 EA per Vent

• Range of Designs with up to 10 Leaves

- Floating Door System (Models 440/660)
- 196mm Hardwood Threshold
- A Choice of Stained Thresholds

Optional Features:

Night Vent Position

Clip Out Sash Detail

FLUSH CASEMENT

Exclusive Features:

Casement Stay

• 90° Concealed Hinae

- Easy Clean Friction Hinge
- Easy Clean Restrictor Hinge
- Auto-Latch Restrictor
- Openable Fixed Sash (Easy to Install)

• Decorative Butt Hinge - BLK/PB/PC/SC

Anti-Warp Clips (Size dependant)

Anti-Prise Clips

Standard Specification:

Depth: 153mm Width: 41mm (Jamb)

Depth: 68mm. Width: 90mm (Stile)

Aluminium 202mm overall*

Operation

Door slides and concertinas left/right Door opens out (Top Rolling Function)

Mechanism

Brio Weatherfold 4S

Non-Mortice Hinge System

Trickle Vent None

Frame Dimensions

Leaf Dimensions

Flush fitting Drop Bolts

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 56mm (Jamb)

Sash Dimensions

Depth: 56mm. Width: 56mm (Stile)

179mm overall (92 + 87mm ext)*

Operation

Window opens outwards Side hung/top hung/fixed (DS)

Mechanism

Handle operated Espag Adjustable locking cams

90° Concealed GU/Uni-Jet Contura Top hung: Easy Clean Friction

Trickle Vent

R13 - 3400 EA per Vent

Standard Specification

Frame Dimensions

Depth: 140mm. Width: 56mm (Jamb)

Sash Dimensions

Depth: 44mm. Width: 44mm (Stile)

140mm overall (flush)*

Operation

Sashes slide up and down Sashes can be fixed

Mechanism

Inline Balances (spring loaded) Rebated into jambs of outer frame

<u>Hinge</u>

N/A

Trickle Vent XS16 - 4600 EA per Vent

Standard Specification:

Frame Dimensions

Depth: 140mm. Width: 110mm (Jamb)

Sash Dimensions Depth: 44mm. Width: 44mm (Stile)

Operation

Sashes slide up and down Sashes can be fixed

140mm overall (flush)*

Mechanism

6mm Cord, Steel/Lead Weights Ball Bearing Sash Pulley

Hinge N/A

Trickle Vent

XS16 - 4600 EA per Vent

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 66mm (Jamb)

Leaf Dimensions Depth: 68mm. Width: 107mm (Stile)

Operation Door opens in or out

Hardwood 140mm overall*

Double handle. Straight through Spindle

Mechanism Handle operated Espag (3 Point)

and Shoot Bolts

SFS Just 3D (Stainless Steel) Adjustable in 3 dimensions

Trickle Vent

R13 - 3400 EA per Vent

p.40

ENTRANCE DOORS

- Swiss Engineered Adjustable 3D Hinge 68mm Deep Door Leaf 92mm Deep Frame Espagnolette Locking (3 Point)
- Laminated Double Glazing Stormguard Aluminium Threshold 22mm Deep Weatherbar Thermally Insulated Panels





Exclusive to the Range:

- A Choice of 14 Classic Styles
- Traditional & Contemporary Profiles
- 32/24mm Laminated Double Glazing
- Mid-Rail: 154mm (Tra)/107mm (Cont)

Optional Features:

- Various Locking Options
- A Range of Bar Designs
- Available as a Double Leaf
- Keyed Alike Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 66mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 107mm (Stile)

Alum + Hardwood 140mm overall*

Operation

Door opens in or out Straight through Spindle

Handle operated Espag (3 Point)

SFS Just 3D (Stainless Steel) Adjustable in 3 dimensions



CREATIVE RANGE

Exclusive to the Range:

- A Choice of 10 Modern Designs
- Smartline Groove
- 29mm Laminated Double Glazing

Optional Features:

- Various Locking Options
- A Range of 4 Veneers
- Available as a Double Leaf
- A Range of Etched Glass
- Keyed Alike Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 66mm (Jamb)

Leaf Dimensions

Depth: 68mm.

Alum + Hardwood 140mm overall*

Operation

Door opens in or out Straight through Spindle

Handle operated Espag (3 Point)

SFS Just 3D (Stainless Steel) Adjustable in 3 dimensions



Heritage Range

Exclusive to the Range:

- A Choice of 10 Traditional Designs
- Deep Timber Panels
- 32mm Laminated Double Glazing
- Mid-Rail: 154mm

Optional Features:

- Various Locking Options
- A Range of Bar/Lead Designs
- Available as a Double Leaf
- Brass Threshold & Hinges
- Keyed Alike Cylinder
- A Choice of Stained Thresholds

Standard Specification:

Frame Dimensions

Depth: 92mm. Width: 66mm (Jamb)

Leaf Dimensions

Depth: 68mm. Width: 107mm (Stile)

Alum + Hardwood 140mm overall*

Operation

Door opens in or out Straight through Spindle

Handle operated Espag (3 Point)

SFS Just 3D (Stainless Steel) Adjustable in 3 dimensions

PEACE OF MIND

Purchasing new windows and doors is a significant investment in your home; they can increase value and change the whole appearance of any property. At Bereco we only supply products that are of the highest levels of security, performance and quality. Importantly we use only the most environmentally sensitive of materials - our 100% FSC® certification is testament to this.

Products are tested in independent UKAS laboratories with our partners Chiltern Dynamics and audited by BM TRADA. Having a test certificate is one thing, consistently manufacturing products to that level of performance and quality is quite another. Bereco is one of only 3 companies in the UK able to achieve such an award, where the criteria are set above all current building regulations.

Our standard product offerings are accredited to the highest standards on security and weather performance and include certifications in BS7950 and PAS 23/24 (see table below)

PRODUCT	BS6375/1/2*	BS7950*	PAS23/24**	BM TRADA Q MARK	FSC 100%
Casement	\bigcirc	\bigcirc		\bigcirc	\bigcirc
Sliding Sash	\bigcirc	\bigcirc		\bigcirc	\bigcirc
Tilt & Turn	\bigcirc	\bigcirc		\bigcirc	\bigcirc
French Door			\bigcirc	\bigcirc	\bigcirc
Entrance Door			\bigcirc	\bigcirc	\bigcirc
Folding Door				\bigcirc	\bigcirc
Patio Door				\bigcirc	\bigcirc

- * Scheme for windows only
- ** Scheme for doors only











A QUALITY PRODUCT SUPPORTED BY EXTENSIVE WARRANTIES

The extent of our testing and certifications mean we can offer excellent warranties across our whole product range.











Rot & Fungal Decay



ENVIRONMENT

F S C

All products across the entire Bereco Range are manufactured using 100% FSC® timber, responsibly sourced from well managed certified forests. We use only the highest quality, engineered, defect free timber to increase product strength and ensure longevity.

We support the introduction of the latest EU Timber Regulation (EUTR) which bans illegally harvested timber from being placed and sold on the EU market. The law now requires a record to be kept of timber supplier, product species, location of origin and amount bought. A risk assessment must also accompany this information to demonstrate the steps that have been taken to reduce the risk of purchasing illegally sourced timber. Our commitment to achieving only the highest possible FSC certification ensures complete traceability and transparency throughout our manufacturing process.

ENERGY


U-values should be an important consideration for any project. Both current and future Building Regulations strive to make new homes more energy efficient and U-values have a significant impact. The lower the U-value, the slower heat will transfer through an element, therefore possessing better insulation properties, keeping house hold bills (heating costs) to a minimum.

The U-value rating or 'overall heat transfer coefficient' measures the total amount of heat that transfers through a buildings fabric. Each element of a building has an individual U-value rating including brick/stone walls, roofing or building openings.

The units used to express U-values are Watts per m² Kelvin (W/m²K). To offer an explanation; Bereco's whole window U-value is 1.37W/m²K which means for every degree of a temperature difference between the air on the surface inside the window and air on the surface outside 1.37 Watts of heat would pass through any m². This calculation is based on standard glass 4/16/4 low-E argon filled units.







Although U-values are a fundamental part of the decision process when purchasing new windows and doors their main focus is on thermal transmissions based around the centre pane performance. The overall performance of the window should be based on a combination of factors which all contribute;

Points to consider;

U-VALUE

The lower the U-value rating the more energy efficient the product is. It should be noted that where a centre-pane U-value (ug) of less than 0.9W/m²K is specified triple glazing would be required to achieve this. Triple glazing is available on our Contemporary Range windows and doors.

WEATHER RATING

An excellent weather rating from third party, independent UKAS centres. All Bereco products are fully sealed and severe weather rated ensuring they keep drafts out of the home, even in the most extreme conditions.

UNIT SPACER

Made from materials with good insulation properties to reduce energy loss. Bereco offers aluminium or warm edge unit spacers manufactured using composite material to achieve optimum performance.

At Bereco we recognise the importance of achieving a balance between architectural sensitivity and window performance. Our product ranges have been specifically designed to incorporate energy saving properties without compromising on aesthetics. This, in essence, is the concept of our Heritage Range, offering a solution for conservation and listed properties with 14mm slimline glazing which looks identical to single glazing whilst saving energy at the same time.

GLASS SPECIFICATION

A variety of glazing options are available with a range of U-values and decibel ratings. Where noise reduction is a consideration Acoustic glass is available on request.

Glass Specification	Unit Size (mm)	Ug Value (W/m² K)	Decibel Rating (dB)
4/16AR/4T Std Float	24	1.1	31
6/20AR/6T Std Float	32	1.1	33
6/20AR/6T Std Float	24	1.2	34
4/14AR/6.5T Safety	24	1.2	34
6.5/12AR/6.5T Safety & Security	24	1.2	33
6.5/16AR/6.5T Safety & Security	29	1.1	33
6.5/20AR/6.5T Safety & Security	32	1.1	33

^{*}Please refer to p.34-42 for glass specification across the product range

BFRC

The British Fenestration Ratings Council (BFRC) has devised a window rating equation based on values for these components. This rating is expressed as a number and is converted into a grade between A and G with A being the most efficient. Bereco have a range of energy ratings available, supported by BM TRADA certifications, which depend on the glass and spacer choice ranging from A-C. The window energy ratings are incorporated into the latest version of Part L Conservation of Fuel and Power Standard and are to become an increasingly referenced rating in specifications.

Window design, an art in itself

In design it is often the subtle, finer touches that can dramatically transform the appearance of an everyday object into a truly beautiful piece.

Flexibility and choice is paramount when selecting the perfect windows and doors to complement a properties interior décor and external façade. Our exclusive Product Range incorporates a wide variety of design options, offering the ideal canvas to create a truly bespoke finish to any property.



Choose your timber

Only 100% FSC engineered defect free, laminated timber is used across the entire product range.

A choice of 3 timber specifications offers flexibility and style:







Softwood (Redwood)

Hardwood

Oak (Dark Red Meranti) (Solid Oak)

Larch Veneer is also available in the Creative Door Range

Try our exclusive range of Heritage Paint Colours

Perfect for complementing period window designs, colours are particularly suited to properties with a stone facade.





Paint it

Introduce a splash of colour with any BS or RAL paint finish to create a truly individual design statement. A comprehensive range of colour options can be selected, ranging from soft neutral tones to bright bold shades.

Stain it

A wide range of stain options are available combined with clear timber to achieve a seamless finish. Stain takes a slightly different appearance dependant on timber specification; grain appears much more prominent on hardwood where softwood results in a smoother finish.

Match it

We can match any Farrow & Ball colour where a traditional finish is desired.



Simple yet Elegant with...Neutrals



Contemporary Sliding Sash Spiral Balance | RAL 9016 Traffic White



Sleek & Subtle with ... Greys



porary Sliding Sash Spiral Balance | RAL 7024 Graphite Grey



Go Bold with ... Brights







H07 Heritage Door Frame: F&B All White Leaf: NCS S 4550-B30-G Turquoise

Frame it

Create a statement entrance with a range of contrasting frame and leaf dual colour options. The frame can be tailored to match the windows and accentuate the colour of the door leaf.



p.47 p.46

Window design, an art in itself

Glazing Patterns


Glazing is an important design element for any project and can make all the difference when creating a feature window or door. A variety of obscure glazing patterns are available with different designs offering varying privacy levels (rated 1-5, 5 being the highest level).

5 Frosted



















4 Kocie 3 Chinchilla



5 Delta



Contemporary Sliding Sash Spiral Balance | Obscure Glazing - Niagara

Leaded Designs

Lead designs transform glazing into a work of art incorporated into a properties exterior. We can replicate traditional or completely bespoke lead patterns to suit your project. Our expert team offers design advice with drawings to help visualise how the final pattern will appear on glazing.

Choose from:

• Antique Black • Silver • Gold • Old Gold Available in 6mm and 9mm

Specialist glazing:


- Painted Glass Stained Glass Bevelled Glass
- Anti-Sun Glass Self Cleaning Glass

Glazing Bar Designs


Bespoke bar arrangements can be supplied to complement any window design without overpowering the windows original aesthetics. The beauty of timber is its versatility, lending itself to the most unique curved and arched bar designs, transforming the whole appearance of a facade. Bereco supply stick on bars with back to back unit spacers creating the illusion of separate panes of glass. Bars as slim as 16mm allow for elegant profiles.

Traditional Lipped Casement | 6mm Antique Black Lead

contemporaryrange



Heritage Glazing Bars can be found on p. 27



p.48

p.49

PRODUCT


Door Panels

Entrance Doors are PAS 23/24 certified and incorporate a 68mm thermally insulated door leaf as standard. An extensive range of panel designs are available across all ranges to create a wide range of unique styles. Deeper panels on the Heritage and Classic designs in the Traditional profile replicate the elegant profiling of original timber doors.




Finishing Touches

Unlike many others in the market we offer a diverse range of finishing touches designed to save time during installation and further enhance the appearance of the window. Supplied factory finished as standard, this ensures the final result is one of quality and consistency.




Cill Horn

Extends either side of the window retaining external character.




Arched Packer

Where infils are required to an arched lintel to create a curved head.




Packer

For use where a reveal is present or where render returns onto the window.



Curved Plate


To give the appearance of cuved glass within a window or door.



Cheeks

Ideal for dormer windows or where tile hanging is featured.

Internal Finishing Touches



Those Little Extras

Bereco offers a variety of additional ancillary items including cavity closers, fixing packs and maintenance products. Cavity Closers ensure window openings are ready for installation whilst fixing packs enable quick and easy fitting. Regular maintenance helps prolong product life and ensures warranties are maintained.



Cavity Closer

Cavity Closers are the simplest, most effective way to seal cavities around wall openings and provide a rigid window or door frame template. As well as acting as a brickwork former, they enhance thermal efficiency, create a damp-proof course and prevent thermal bridging in accordance with Part L regulations.

- 3 sided insulated Cavity Closer
- Cavities between 50mm-300mm
- Easy to install
- 12 brick ties per item included
- Thermally efficient
- Prevents cold bridging



Fixing Pack

At Bereco we recommend the use of fixing packs ensuring all components are to hand, enabling quicker installation.



Maintenance Product

Our special clean and care system will restore shine to windows and doors whilst improving performance and maintaining all important warranties.

IRONMONGERY

Its all in the detail

Ironmongery choice can dramatically enhance the overall appearance of any window or door design whilst adding unique style to a property. We offer a diverse collection ranging from contemporary Italian designs to antique old English period styles. The images below showcase an inspirational selection of furniture to complement both external aesthetics and interior décor.

Antique Black

A rustic finish to further enhance traditional character and charm.



BE1010BK Black Monkey Tail Casement Handle



KP2587 Sash Hook lift



KP0171B Casement Stay



1083 Letter Plate

BA1110



KP782AB Ring Door Knocker

KP3372AB



KP2462AB Fleur de Lys Door Handle



Fleur de Lys Letter Plate

KP1005AB Doctors Door Knocker



KP1979AB 3" Numerals



DF3025AB Trelissik Door Handle

Brass

A range of Polished Brass furniture gives a classic touch.

KP1460

Sash Fastener



DF2705PB

Octagonal Door Knob

DF2402PB Laurin Pull Handle



DF2370PB Cast Pull Handle



DF2655PB Ring Knocker



BE1015PB BE1000PB Bulb End Handle Monkey Tail Handle



DF2430 Victorian Pull Handle



DF2602PB Victorian Knocker



Beehive Sash Fastener

Satin Stainless Steel

For the most Contemporary projects where an urban finish is desired.



Tilbrook Door Handle



DF5580SSS Victorian Letter Plate



DF3045SSS Cragside Door Handle



DF1574SSS

Round Euro Escutcheon

JSS1235LH Round Bar Casement Handle

p.52



DF5600SSS Finger Plate

DF5594SSS

Straight Pull Handle

Polished Chrome

A high-shine reflective finish ideal for modern living spaces.



Euro Cylinder Pull

Square Euro Escutcheon

BD04EPC

DF2260PC

Victorian Letter Plate

BE1015PC

Bulb End Handle



Twist Door Handle



Luxury Door Handle



ZPZ080PC Round Euro Escutcheon Amalfi Door Handle



DF2655PC Ring Door Knocker



BE1010PC Monkey Tail Handle



DF2315PC

DF2320PC

Curved Pull Handle

Octagonal Door Knob

Straight Pull Handle

Sash Angel Venlock™



DF3022PC Balmoral Swan Door Handle

Duo

A combination of Polished and Satin Chrome for a truly unique finish.





DF1360DUO Baggs Door Handle



Venice Door Handle

Satin Chrome

A sleek matt finish particularly suited to modern styles.



ZPZ070SC Venice Door Handle



Centre Door Knob



Victorian Letter Plate



BE1015SC Bulb End Handle

Pewter

DF2802SC

A superior product manufactured using only the finest lead-free pewter.



FDMP01PW Durham Door Handle





Jesmond Door Handle

FD000CPW Euro Profile Escutcheon




Pewter Letter Plate

Create your own Wish List View all selected items in one print ready, downloadable document. www.bereco.co.uk










Cill Extension Options - Available across all products

Cill Extensions available in a range of sizes to suit specific requirements.

Sizes 100mm and above are supplied in Hardwood timber.



PRODUCTS AVAILABLE ACROSS EACH RANGE

	contemporaryrange	Traditional Range	Heritage Range
Lipped Casement	Ø	Ø	
Flush Casement	 	Ø	Ø
Tilt & Turn	Ø	Ø	
Sliding Sash Inline Spiral Balance	Ø	Ø	Ø
Sliding Sash Cords & Weights	Ø	Ø	Ø
Lipped French Door	Ø	Ø	
Flush French Door	 	Ø	Ø
Folding Sliding Door	Ø	Ø	
HS Patio Door	Ø	Ø	

	contemporary Profile	Traditional Profile	Heritage Profile
Classic Entrance Door	Ø	Ø	
CREATIVE Entrance Door	Ø		
Heritage Entrance Door	 		Ø











CHECK OUT OUR WEBSITE

www.bereco.co.uk

Inspirational Gallery

The inspirational gallery area enables you to visualise which bespoke products would best suit your property. A vast number of photographs are available to view on our website and can be filtered by product type to display a diverse range of images from across all ranges.



Resource Centre

A business to business tool specifically designed to equip you with all the information needed to better understand our diverse product range. Login to access technical information including CAD drawings in DWG, DXF & PDF format, marketing & promotional materials and product photographs in high resolution and optimised for web use.

VISIT OUR SHOWROOM

We have now opened the doors to our innovative showroom, displaying our latest Heritage and Creative entrance door ranges and collection of ironmongery.

We welcome you to come and browse our bespoke window & door designs and suited ironmongery to gain inspiration for your project. Whether you are replacing windows and doors in a period property or designing a high specification new build project, we have the ideal product to match your specific requirements. Our highly experienced staff will be happy to guide you through the process, providing information on product specification, specific aesthetic features and discussing design options.

Please contact a member of the Bereco team today to arrange your viewing.

t: 01709 838 188





Bereco Limited
Unit 5 Aspen Court,
Centurion Business Park,
Bessemer Way,
Rotherham,
South Yorkshire S60 1FB
t: 01709 838 188 f: 01709 838 330

e: enquiries@bereco.co.uk

Bereco Retail Limited
Unit 4 Aspen Court,
Centurion Business Park,
Bessemer Way,
Rotherham,
South Yorkshire S60 1FB
t: 01709 377 406 f: 01709 379 586
e: enquiries@berecoretail.co.uk

