

Kömmerling Premiline Patio Door

Smooth sliding operation with stylish looks

Standard Specification (includes glazing):



- · Black gaskets with woolpile weatherseals
- · White (chrome and gold effect upgrades) handles
- · Six point six hook locking
- · Fully welded and reinforced
- Stainless steel adjustable rollers on a stainless steel track
- · Slides on outer track as standard inner track on request
- 28mm toughened sealed units with Low E Argon gas and warm edge spacer
- PVCU profiles using 'greenline' 100% lead free stabilizer
- · Full height aluminium 'pull grip' available
- 20mm low aluminium threshold available lower weather rating
- · Mechanically jointed outer frame available

Triple Track "Premiline"

Middle pane is automatically moved when fully opening both panes. Only available in white, 139mm front to back frame dimension (no cill or trickle vent options available).



20mm low aluminium threshold







NB: The height of the sash must not be more than 2.5 times larger than the width e.g. Frame height 2090mm means minimum frame width of 1600mm

PAS24 upgrade - 'Lifetime Homes' and Document Q compliant

PAS24 test data based on 2 pane patio door at 2450mm wide x 2260mm high

- A Shootbolt keep with nightvent facility
- B Shootbolt
- C Top rail 'dog bolt' keep
- D Top rail 'dog bolt'
- E Interlock handle White, Black, Chrome
- F Interlock hook bolts (x3)
- G Interlock keeps (x3)
- H Sash hook locks (x8)

NB: Double shootbolt option only available on doors above 2070mm frame height

Foil Options


Standard Foils

Available both sides or on smooth white









Black



Cream

Irish Oak



NB: Foiled on White profiles will show white on the insides of the head and base outer frame

Anthracite Grey



Chartwell Green

Cream both sides only (white base)